

# CTP Product Guide For Brick Ties With Varying Cavities

(Standard 3-5/8" Brick)

Cavity Range **	CTP-16 Base Plate Without Insulation														
	CTP 16-0			CTP 16-1"			CTP 16-2"			CTP 16-3"			CTP 16-4"		
	CTP-WT Tie Size Required			CTP-WT Tie Size Required			CTP-WT Tie Size Required			CTP-WT Tie Size Required			CTP-WT Tie Size Required		
	3"	4"	5"	3"	4"	5"	3"	4"	5"	3"	4"	5"	3"	4"	5"
3/4" – 1 3/4"	●														
1 1/4" – 2 3/4"		●		●											
2 1/4" – 3 3/4"			●		●		●								
3 1/4" – 4 3/4"						●		●		●					
4 1/4" – 5 3/4"									●		●		●		
5 1/4" – 6 3/4"												●		●	
6 1/4" – 7 3/4"															●

\*\* Cavity is defined as the distance between the inside face of veneer to the back-up.  
When using insulation, select the base plate size greater than or equal to insulation thickness.



**CONSTRUCTION TIE PRODUCTS**

7974 W. Orchard Drive • Michigan City, Indiana 46360-9390 • USA

Phone: (219) 878-1427 • Fax: (219) 874-3626

Email: [stevectp@comcast.net](mailto:stevectp@comcast.net) • [www.ctpanchors.com](http://www.ctpanchors.com)

*Engineered Anchoring Solutions Provider*

